



TYRE CATALOGUE



KING OF TYRES

ATTITUDE IS THE PRODUCT OF BELIEF

AGR

POWERED BY



WWW.ETD.NL



THE POWER OF LEAO TYRES

As the King of Tyres, LEAO offers you the perfect tyres to rule any terrain. Whether you are looking for TBR, AGR or OTR tyres, LEAO tyres guarantee economical prices, excellent quality and 100% reliability.

The lion in the logo reflects exactly what it is all about: the excellent, nearly “royal” capabilities provided by LEAO tyres. LEAO tyres match the requirements and desires of many different users perfectly and they have proven their value on all types of surfaces and under all weather conditions.

The broad range of modern LEAO patterns is continuously adapted to the demands of the European market. This makes LEAO a brand with state-of-the-art patterns ready to attack the terrain.

If you are looking for an excellent value-for-money option, LEAO tyres is the brand to choose as nothing beats a lion!

More information: www.leao-tyres.com



PATTERN OVERVIEW



LR861 (R-1W)

PAGE 6



LR700

PAGE 7



LR650

PAGE 8



LR7000

PAGE 9



LR8000

PAGE 9



LR861 (ROW CROP)

PAGE 10



LR9000

PAGE 10



T820

PAGE 11



ADM991

PAGE 11



LLA38

PAGE 11



MPT30

PAGE 12



AD702

PAGE 12



FL300

PAGE 13



LBI301

PAGE 13



LR451

PAGE 14



LR400

PAGE 14

TABLE OF CONTENTS

PATTERN	DESCRIPTION	PAGE
---------	-------------	------

Tractor Tyres

LR861	Tractor Radial Agricultural Tyre	6
LR700	Tractor Radial Agricultural Tyre	7
LR650	Tractor Radial Agricultural Tyre	8
LR7000	Tractor Radial Agricultural Tyre	9

Harvester Tyres

LR8000	Harvester Radial Agricultural Tyre	9
--------	------------------------------------	---

Sprayer Tyres

LR861	Tractor Radial Row Crop Agricultural Tyre	10
LR9000	Sprayer Radial Agricultural Tyre	10

Trailer Tyres

T820	AGR Trailer Tyres	11
ADM991	AGR Trailer Tyres	11
LLA38	AGR Trailer Tyres	11
MPT30	Tractor Radial Agricultural Tyre	12
AD702	Strong-Max Steel Belted	12
FL300	Flo-Max Flotation Steel Belted	13
LBI301	Trailer Radial Agricultural Tyre	13

Compact Line

LR451	Compact Line Radial Agricultural Tyre	14
LR400	Strong-Max Industrial Tractor MPT	14

Disclaimer

The information in this brochure is based on our manufacturer's specifications. This information is for general information purposes only. Any reliance you place on the information shown in this brochure is therefore strictly at your own risk. European Tyre Distributors is not liable for any loss or damage arising from the use of this brochure.

LR861

TRACTOR RADIAL AGRICULTURAL TYRE

- BETTER TRACTION AND BRAKING PERFORMANCE
- SAVES WORK, TIME AND FUEL
- BETTER RUNNING STABILITY
- SUITABLE FOR MODERN MECHANICAL EQUIPMENT



SIZE	SIZE	LOAD INDEX	SPEED INDEX	TL/TT	RIM	MAX. LOAD 40 KM/H (KG)	MAX. LOAD 50 KM/H (KG)	INFLATED PRESSURE (KPA)	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	STATIC LOAD RADIUS (MM ± 2.5%)	ROLLING CIRCUM-FERENCE (MM ± 2.5%)	TREAD DEPTH (MM)	NUMBER OF LUGS
280/85R24	11.2R24	115/112	A8/B	TL	W9, W10	1215	1120	160	1086	282	497	3247	39	19x2
320/85R24	12.4R24	122/119	A8/B	TL	W9, W10, W11	1500	1360	160	1154	319	527	3446	41	19x2
340/85R24	13.6R24	125/122	A8/B	TL	W11, W12	1650	1500	160	1188	343	544	3555	42	19x2
380/85R24	14.9R24	131/128	A8/B	TL	W11, W12, W13	1950	1800	160	1256	380	573	3745	45	19x2
420/85R24	16.9R24	137/134	A8/B	TL	W13, W14L, W15L	2300	2120	160	1324	418	604	3950	48	19x2
320/85R28	12.4R28	124/121	A8/B	TL	W9, W10, W11	1600	1450	160	1255	319	573	3748	41	20x2
340/85R28	13.6R28	127/124	A8/B	TL	W11, W12	1750	1600	160	1289	343	589	3851	42	20x2
380/85R28	14.9R28	133/130	A8/B	TL	W11, W12, W13	2060	1900	160	1357	380	619	4047	45	20x2
420/85R28	16.9R28	144/144	A8/B	TL	W13, W14L, W15L	2800	2800	240	1425	418	651	4252	48	20x2
380/85R30	14.9R30	135/132	A8/B	TL	W11, W12, W13	2180	2000	160	1408	380	642	4199	45	20x2
420/85R30	16.9R30	140/137	A8/B	TL	W13, W14L, W15L	2500	2300	160	1476	418	675	4415	48	20x2
460/85R30	18.4R30	145/142	A8/B	TL	W14L, W15L, W16L	2900	2650	160	1544	455	707	4618	51	20x2
320/85R32	12.4R32	142/139	A8/B	TL	W9, W10, W11	2650	2430	400	1357	319	606	4039	41	21x2
380/85R34	14.9R34	147/147	A8/B	TL	W11, W12, W13	2960	2960	300	1510	380	677	4518	45	21x2
420/85R34	16.9R34	142/139	A8/B	TL	W13, W14L, W15L	2650	2430	160	1578	418	724	4729	48	21x2
460/85R34	18.4R34	147/144	A8/B	TL	W14L, W15L, W16L	3075	2800	160	1646	455	755	4932	51	21x2
320/85R36	12.4R36	128/125	A8/B	TL	W9, W10, W11	1800	1650	160	1458	319	656	4376	41	22x2
340/85R36	13.6R36	132/129	A8/B	TL	W11, W12	2000	1850	160	1492	343	675	4512	42	22x2
340/85R38	13.6R38	133/130	A8/B	TL	W11, W12	2060	1900	160	1543	343	714	4666	42	22x2
420/85R38	16.9R38	144/141	A8/B	TL	W13, W14L, W15L	2800	2575	160	1679	418	771	5037	48	22x2
460/85R38	18.4R38	149/146	A8/B	TL	W14L, W15L, W16L	3250	3000	160	1747	455	802	5243	51	22x2
520/85R38	20.8R38	155/152	A8/B	TL	DW16L	3875	3550	160	1849	516	847	5533	54	22x2
460/85R42	18.4R42	150/147	A8/B	TL	W14L, W15L, W16L	3350	3075	160	1849	455	818	5452	51	23x2
480/80R42	18.4R42	156/156	A8/B	TL	DD16L, DW16L, W16L, DW16A*, W16A*	4000	4000	240	1835	479	826	5507	49	22x2
520/85R42	20.8R42	157/154	A8/B	TL	DW16L, DW18L	4125	3750	160	1951	516	898	5868	54	23x2
420/80R46	16.9R46	151/148	A8/B	TL	W12, W13	3450	3150	240	1840	418	828	5522	47	25x2
480/80R46	18.4R46	158/158	A8/B	TL	DD16L, DW16L, W16L, DW16A*, W16A*	4250	4250	240	1936	479	894	5846	49	23x2

LR700

TRACTOR RADIAL AGRICULTURAL TYRE

- SAVES TIME AND FUEL
- BETTER SELF-CLEANING CAPABILITY
- COMFORT ON THE ROAD AND IN THE FIELD



SIZE	LOAD INDEX	SPEED INDEX	TL/ TT	RIM	MAX. LOAD 40 KM/H (KG)	MAX. LOAD 50 KM/H (KG)	INFLATED PRESSURE (KPA)	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	STATIC LOAD RADIUS (MM ± 2.5%)	ROLLING CIRCUM-FERENCE (MM ± 2.5%)	TREAD DEPTH (MM)	NUMBER OF LUGS
360/70R24	122/119	A8/B	TL	W10, W11, W12	1500	1360	160	1152	357	525	3430	42	19x2
360/70R24	127/124	A8/B	TL	W10, W11, W12	1750	1600	240	1152	357	519	3430	42	19x2
380/70R24	125/125	A8/B	TL	W11, W12, W13	1650	1650	160	1190	380	537	3581	43	18X2
420/70R24	130/127	A8/B	TL	W12, W13, W14L	1900	1750	160	1248	418	559	3728	44	17x2
420/70R24	136/133	A8/B	TL	W12, W13, W14L	2240	2060	240	1248	418	559	3728	44	17x2
480/70R24	138/135	A8/B	TL	W14L, W15L, W16L	2360	2180	160	1316	479	592	3949	47	16x2
420/70R28	139/136	A8/B	TL	W12, W13, W14L	2430	2240	240	1349	418	607	4048	44	18x2
480/70R28	140/137	A8/B	TL	W14L, W15L, W16L	2500	2300	160	1421	479	635	4236	47	17x2
480/70R34	143/143	A8/B	TL	W14L, W15L, W16L	2725	2725	160	1580	479	712	4746	47	18x2
480/70R38	145/142	A8/B	TL	W14L, W15L, W16L	2900	2650	160	1681	479	757	5045	47	19x2
520/70R38	150/150	A8/B	TL	W15L, W16L, W18L	3350	3350	160	1749	516	816	5440	48	19x2
580/70R38	155/155	A8/B	TL	W18L	3875	3875	160	1827	577	836	5571	50	18x2
580/70R38	170/167	A8/B	TL	W18L	6000	5450	280	1827	577	836	5571	50	18x2

LR650

TRACTOR RADIAL AGRICULTURAL TYRE

- LONGER SERVICE LIFE
- EXCELLENT STABILITY AND COMFORT
- MORE EFFICIENT TRACTION
- OUTSTANDING FLOATING BEHAVIOR REDUCES PRESSURE TO LAND



SIZE	LOAD INDEX	SPEED INDEX	TL/TT	RIM	MAX. LOAD 40 KM/H (KG)	MAX. LOAD 65 KM/H (KG)	INFLATED PRESSURE (KPA)	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	STATIC LOAD RADIUS (MM ± 2.5%)	ROLLING CIRCUM-FERENCE (MM ± 2.5%)	TREAD DEPTH (MM)	NUMBER OF LUGS
440/65R24	131/128	A8/D	TL	W13, W14L, W15L	1950	1800	160	1182	441	528	3519	45	19x2
480/65R24	136/133	A8/D	TL	W14L, W15L	2240	2060	160	1234	479	611	3000	46	19x2
540/65R24	143/140	A8/D	TL	W16L, W18L	2725	2500	160	1312	550	581	3873	48	19x2
440/65R28	134/131	A8/D	TL	W13, W14L, W15L	2120	1950	160	1283	441	577	3838	45	20x2
480/65R28	139/136	A8/D	TL	W14L, W15L	2430	2240	160	1335	479	596	3970	46	20x2
540/65R28	145/142	A8/D	TL	W16L, W18L	2900	2650	160	1413	550	633	4223	48	20x2
600/65R28	150/147	A8/D	TL	DW20B, W18L	3350	3075	160	1491	591	671	4387	52	18x2
540/65R30	153/150	A8/D	TL	W16L, W18L	3650	3350	240	1464	550	653	4353	48	20x2
540/65R34	148/145	A8/D	TL	W16L, W18L	3150	2900	160	1566	550	698	4655	48	21x2
600/65R34	160/157	A8/D	TL	DW20B, W18L	4500	4125	240	1644	591	756	4974	52	20x2
540/65R38	156/153	A8/D	TL	W16L	3995	3650	240	1667	550	767	5085	48	21x2
600/65R38	156/153	A8/D	TL	DW20B, W18L	4000	3650	160	1745	591	769	5129	52	20x2
650/65R38	160/157	A8/D	TL	DW20B	4500	4125	160	1811	645	807	5380	56	20x2
710/70R38	169/166	A8/D	TL	DW23B	5800	5300	160	1959	716	873	5818	57	19x2
650/65R42	168/165	A8/D	TL	DW20B	5600	5150	240	1913	645	858	5722	56	21x2
710/70R42	171/168	A8/D	TL	DW23B	6150	5600	160	2061	716	944	6166	57	20x2
710/70R42	176/173	A8/D	TL	DW23B	7100	6500	240	2061	716	944	6166	57	20x2

LR7000

TRACTOR RADIAL AGRICULTURAL TYRE

- ENHANCED BEAD STRENGTH
- LONGER SERVICE LIFE
- EXCELLENT STABILITY AND COMFORT
- MORE EFFICIENT TRACTION
- OUTSTANDING FLOATING BEHAVIOR REDUCES PRESSURE TO LAND



SIZE	LOAD INDEX	SPEED INDEX	TL/TT	RIM	MAX. LOAD 50 KM/H (KG)	INFLATED PRESSURE (KPA)	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	STATIC LOAD RADIUS (MM ± 2.5%)	ROLLING CIRCUM-FERENCE (MM ± 2.5%)	TREAD DEPTH (MM)	NUMBER OF LUGS
600/70R28	161/161	A8/B	TL	DW18L, DW20B, W18L	4625	280	1551	591	698	4610	52.5	19x2
600/70R30	158	D	TL	DW18L, DW20B, W18L	4460	240	1602	591	720	4752	52.5	19x2
600/70R30	152	D	TL	DW18L, DW20B, W18L	3725	160	1602	591	720	4752	52.5	19x2
710/55R30	153/156	D/A8	TL	DW23B, DW24B	3830	160	1544	706	705	4650	51	18x2
600/70R34	160/163	D/A8	TL	DW18L, DW20B, W18L	4725	240	1704	601	796	5130	52	21x2
650/60R34	159/162	D/A8	TL	DW20B, DW21B, DW23B	4590	240	1644	645	773	5066	52	19x2
650/85R38	173/176	D/A8	TL	DW23B, DW20B, DW21B	6825	240	2071	645	915	6225	65	21x2
800/70R38	178/181	D/A8	TL	DW25B	7875	240	2085	798	944	6284	62	19x2
620/70R42	172	D	TL	DW18L, DW20B, W18L	6615	320	1935	625	887	5789	58	22x2
710/75R42	181/184	D/A8	TL	DW23B, DW21B	8660	320	2133	706	991	6461	63	20x2

LR8000

HARVESTER RADIAL AGRICULTURAL TYRE

- LONGER SERVICE LIFE
- EXCELLENT STABILITY AND COMFORT
- MORE EFFICIENT TRACTION
- OUTSTANDING FLOATING BEHAVIOR REDUCES PRESSURE TO LAND



SIZE	LOAD INDEX	SPEED INDEX	TL/TT	RIM	MAX. LOAD 50 KM/H (KG)	INFLATED PRESSURE (KPA)	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	STATIC LOAD RADIUS (MM ± 2.5%)	ROLLING CIRCUM-FERENCE (MM ± 2.5%)	TREAD DEPTH (MM)	NUMBER OF LUGS
750/65R26	171/171	A8/B	TL	DW23B, DW24B, DW25B	6150	320	1636	754	704	4815	50	19x2
650/75R32	172/172	A8/B	TL	DW20B, DW21B, DW23B	6300	320	1789	645	807	5378	59	21x2
800/65R32	181/181	A8/B	TL	DW25B, DW27B, DH27B	8250	360	1853	798	810	5400	58	20x2
800/70R32	181/181	A8/B	TL	DW25B, DW27B, DH27B	8250	320	1933	798	856	5783	57	22x2

LR861

TRACTOR RADIAL ROW CROP AGRICULTURAL TYRE

- BETTER TRACTION AND BRAKING PERFORMANCE
- SAVES WORK, TIME AND FUEL
- BETTER RUNNING STABILITY
- SUITABLE FOR MODERN MECHANICAL EQUIPMENT



SIZE	SIZE	LOAD INDEX	SPEED INDEX	TL/ TT	RIM	MAX. LOAD 40 KM/H (KG)	MAX. LOAD 50 KM/H (KG)	INFLATED PRESSURE (KPA)	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	STATIC LOAD RADIUS (MM ± 2.5%)	ROLLING CIRCUM-FERENCE (MM ± 2.5%)	TREAD DEPTH (MM)	NUMBER OF LUGS
420/90R30	16.9R30	142/139	A8/B	TL	DW13, W14L	2650	2430	160	1518	418	683	4556	48	20x2
420/90R30	16.9R30	147/144	A8/B	TL	DW13, W14L	3075	2800	240	1518	418	683	4556	48	20x2
320/90R46	12.4R46	146/143	A8/B	TL	W9, W10, W11	3000	2725	320	1744	319	785	5234	37	33x2
320/90R46	12.4R46	148/148	A8/B	TL	W9, W10, W11	3150	3150	320	1744	319	785	5234	37	33x2
380/90R46	14.9R46	149/149	A8/B	TL	W11, W12, W13	4125	4125	360	1852	380	858	5609	45	25x2
380/90R46	14.9R46	157/157	A8/B	TL	W11, W12, W13	4125	4125	360	1852	380	858	5609	45	25x2

LR9000

SPRAYER RADIAL AGRICULTURAL TYRE

- BETTER SOIL PROTECTION
- EXCEPTIONAL LOAD CAPACITY



SIZE	LOAD INDEX	SPEED INDEX	TL/ TT	RIM	MAX. LOAD 40 KM/H (KG)	INFLATED PRESSURE (KPA)	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	STATIC LOAD RADIUS (MM ± 2.5%)	ROLLING CIRCUM-FERENCE (MM ± 2.5%)	TREAD DEPTH (MM)	NUMBER OF LUGS
380/90R50	160/157	A8/B	TL	W11, W12, W13	4500	400	1954	380	910	5808	48	36x2

AGR TRAILER

- SELF-CLEANING
- STRONG LATERAL STABILITY
- EXCELLENT SUITABILITY FOR ON- AND OFF-ROAD USE
- RETREADABLE

T820

SIZE	SIZE	LOAD INDEX	SPEED INDEX	TL/TT	RIM	MAX. LOAD 40 KM/H (KG)	INFLATED PRESSURE (KPA)	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	STATIC LOAD RADIUS (MM ± 2.5%)	ROLLING CIRCUM-FERENCE (MM ± 2.5%)	TREAD DEPTH (MM)
385/55R19.5	T820	156	D	TL	13	4000	900	914	382	423	2872	12.5
435/50R19.5	T820	160	D	TL	14	4500	900	926	433	428	2908	12.5
445/45R19.5	T820	160	D	TL	14	4500	900	899	444	412	2824	16



ADM991

SIZE	SIZE	LOAD INDEX	SPEED INDEX	TL/TT	RIM	MAX. LOAD 40 KM/H (KG)	INFLATED PRESSURE (KPA)	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	STATIC LOAD RADIUS (MM ± 2.5%)	ROLLING CIRCUM-FERENCE (MM ± 2.5%)	TREAD DEPTH (MM)
445/45R19.5	ADM991	164	D	TL	13, 14	5000	900	910	425	415	2757	16
385/65R22.5	ADM991	164	D	TL	11.75	5000	900	1073	389	496	3251	16



LLA38

SIZE	SIZE	LOAD INDEX	SPEED INDEX	TL/TT	RIM	MAX. LOAD 40 KM/H (KG)	INFLATED PRESSURE (KPA)	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	STATIC LOAD RADIUS (MM ± 2.5%)	ROLLING CIRCUM-FERENCE (MM ± 2.5%)	TREAD DEPTH (MM)
425/65R22.5	LLA38	165	D	TL	13	5150	900	1120	421	498	3520	17.5
445/65R22.5	LLA38	169	D	TL	13	5800	900	1148	435	521	3605	18



MPT30

TRACTOR RADIAL AGRICULTURAL TYRE

- FUEL EFFICIENT
- COMFORT ON THE ROAD AND IN THE FIELD
- EXCELLENT HANDLING
- GREAT WEAR AND PUNCTURE RESISTANCE



SIZE	LOAD INDEX	SPEED INDEX	TL/ TT	RIM	MAX. LOAD 100 KM/H (KG)	INFLATED PRESSURE (KPA)	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	STATIC LOAD RADIUS (MM ± 2.5%)	ROLLING CIRCUM-FERENCE (MM ± 2.5%)	TREAD DEPTH (MM)
355/60R18	142	J	TL	11	2650	500	883	353	398	2694	7.5

AD702

STRONG-MAX STEEL BELTED

FLOTATION RADIAL TYRES FOR SLURRY TANKER, DUMPER TRUCKS AND TRAILERS FOR AGRICULTURAL AND CONSTRUCTION USE

- REINFORCED DESIGN FOR HIGH RESISTANCE
- ALLOWED UP TO 80 KM/H
- STEEL CARCASS WITH ROBUST TREADING AGAINST PUNCTURES AND CUTS
- OFFSET ARRANGED PROFILE BLOCK FOR HIGH TRACTION, EXCEPTIONAL SELF-CLEANING AND EASIER MANOEUVRABILITY ON CHALLENGING GROUND



SIZE	LOAD INDEX	SPEED INDEX	TL/ TT	RIM	MAX. LOAD (KG)	INFLATED PRESSURE (KPA)	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	STATIC LOAD RADIUS (MM ± 2.5%)	ROLLING CIRCUM-FERENCE (MM ± 2.5%)	TREAD DEPTH (MM)
24R20.5	176	F	TL	18	7100	600	1370	600	620	4070	21

FL300 FLO-MAX

FLOTATION STEEL BELTED

RADIAL AGRICULTURAL TYRE FOR TRAILER USE

- STEEL BELTED
- WEAR AND PUNCTURE RESISTANCE
- EXCELLENT GRIP SELF-CLEANING PERFORMANCE



SIZE	LOAD INDEX	SPEED INDEX	TL/TT	RIM	MAX. LOAD 40 KM/H (KG)	MAX. LOAD 65 KM/H (KG)	INFLATED PRESSURE (KPA)	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	STATIC LOAD RADIUS (MM ± 2.5%)	ROLLING CIRCUMFERENCE (MM ± 2.5%)	TREAD DEPTH (MM)
500/50R17	149	D	TL	16.00	4420	3250	500	932	503	421	2860	15
500/45R22.5	146	D	TL	AG16.00	4080	3000	400	1022	503	468	3119	21
500/60R22.5	155	D	TL	AG16.00	5270	3875	400	1172	503	534	3563	18
560/45R22.5	152	D	TL	AG16.00	4825	3550	400	1076	543	488	3258	18
560/60R22.5	165	D	TL	AG16.00	7000	5150	500	1244	543	564	3762	18
580/65R22.5	166	D	TL	AG18.00	7205	5300	400	1326	577	585	3946	21
600/50R22.5	163	D	TL	AG18.00	6630	4875	500	1172	591	546	3586	21
600/55R26.5	165	D	TL	AG20.00	7000	5150	400	1333	591	613	4066	20
650/55R26.5	169	D	TL	AG20.00	7885	5800	400	1389	645	639	4234	24
650/65R26.5	174	D	TL	AG20.00	9110	6700	400	1519	645	697	4646	24
710/50R26.5	170	D	TL	AG24.00	8160	6000	400	1383	727	636	4218	24
750/45R26.5	170	D	TL	AG24.00	8160	6000	400	1349	754	613	4140	25
800/45R26.5	174	D	TL	AG26.00	9110	6700	400	1393	808	615	4178	26
710/50R30.5	173	D	TL	AG20.00	8840	6500	400	1485	727	682	4548	26
750/60R30.5	181	D	TL	AG24.00	11220	8250	400	1675	754	725	5042	26
800/45R30.5	176	D	TL	AG26.00	9655	7100	400	1495	808	657	4450	26

LBI301

TRAILER RADIAL AGRICULTURAL TYRE

- STEEL BELTED
- GREAT WEAR AND PUNCTURE RESISTANCE
- GOOD GRIP AND SELF-CLEANING PERFORMANCE



SIZE	LOAD INDEX	SPEED INDEX	RIM	MAX. LOAD 40 KM/H (KG)	MAX. LOAD 65 KM/H (KG)	INFLATED PRESSURE (KPA)	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	STATIC LOAD RADIUS (MM ± 2.5%)	ROLLING CIRCUMFERENCE (MM ± 2.5%)	TREAD DEPTH (MM)	NUMBER OF LUGS
600/50R22.5	159	D	AG20.00	4790	4375	400	1172	611	510	3470	25.0	28x2
650/65R30.5	176	D	AG20.00	9655	7100	400	1621	645	745	4940	32	36x2
850/50R30.5	182	D	AG28.00	11560	8500	400	1625	862	747	4955	32	36x2

LR451

COMPACT LINE RADIAL AGRICULTURAL TYRE

- INCREASED TRACTION PERFORMANCE
- ENHANCED SHOULDER WEAR AND CUT RESISTANCE
- ENHANCED TREAD WEAR RESISTANCE



SIZE	SIZE	LOAD INDEX	SPEED INDEX	TL/ TT	RIM	MAX. LOAD 50 KM/H (KG)	INFLATED PRESSURE (KPA)	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	STATIC LOAD RADIUS (MM ± 2.5%)	ROLLING CIRCUMFERENCE (MM ± 2.5%)	TREAD DEPTH (MM)	NUMBER OF LUGS
460/70R24	17.5LR24	152/152	A8/B	TL	DW14L, DW15L, DW16L	3550	320	1254	455	555	3700	36	18x2
460/70R24	17.5LR24	159/159	A8/B	TL	DW14L, DW15L, DW16L	4375	400	1254	455	556	3709	36	18x2
500/70R24	19.5LR24	164/164	A8/B	TL	DW16L, DW15L	5000	400	1310	503	593	3899	39	18x2

LR400

STRONG-MAX INDUSTRIAL TRACTOR MPT

- INCREASED TRACTION PERFORMANCE
- CUT RESISTANT DUE TO ENHANCED SHOULDER DESIGN
- EXCELLENT TREAD WEAR RESISTANCE



SIZE	SIZE	LOAD INDEX	SPEED INDEX	TL/ TT	RIM	MAX. LOAD 50 KM/H (KG)	INFLATED PRESSURE (KPA)	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	STATIC LOAD RADIUS (MM ± 2.5%)	ROLLING CIRCUMFERENCE (MM ± 2.5%)	TREAD DEPTH (MM)
400/70R18	-	147/147	A8/B	TL	11, 12, 13	2575	380	1017	404	463	3087	23
405/70R18	-	153/141	A2/B	TL	11, 12, 13	2575	380	1025	407	471	3124	20
400/70R20	-	149/149	A8/B	TL	11, 12, 13, 14	3250	400	1068	404	486	3238	20
405/70R20	-	155/143	A2/B	TL	11, 12, 13, 14	2725	380	1076	407	495	3279	20
500/70R24	19.5R24	164/164	A8/B	TL	DW16	5000	400	1310	503	593	3899	24



**IT'S
GOOD
TO BE
THE
KING!**

KING OF TYRES

ATTITUDE IS THE PRODUCT OF BELIEF



ETD - YOUR WHOLESALE FOR THE COMPLETE PACKAGE

European Tyre Distributors B.V. (ETD) specializes in the import of Asian tyres for the European market, with the brands LEAO and Security as its flagships. Due to the well-established partnerships with top Asian manufacturers ETD can guarantee the quick supply of high quality products straight from Asia or from ETD's 20.000 m² of warehouses near Rotterdam, the Netherlands.

While ETD's core business is tyres, in all different ranges and sizes, they also offer a good selection of accompanying products such as tubes and wheels. ETD therefore is a reliable partner in TBR, AGR, OTR, PCR but also in niche markets such as trailer, industrial and crossply tyres.

Next to their substantial range, ETD is also known for its great service. With forty years of experience they are able to provide the best advice tailored to the customers' specific requests.

Overall, European Tyre Distributors stands for a large range of quality tyres, competitive prices and a level of service that surpasses international competition.

CONTACT

European Tyre Distributors B.V.
P.O. Box 5722, 3291 AA Strijen, The Netherlands
Industriestraat 12, 3291 CC Strijen, The Netherlands

Tel: + 31 (0)78 629 1210
Email: sales@etd.nl
www.etd.nl